

## Report for NU319-E-XL-M1-C3 All results refer to continuous 24/7 operation.

### Input

Bearing data	
Designation	NU319-E-XL-M1-C3
Design	Cylindrical roller bearing, rib-guided, with cage
Series	NU3-E
Basic load ratings	
Basic static load rating (C0)	380.000 N
Basic dynamic load rating (C)	390.000 N

Load	
Load levels	moderate (C0/P approx. 10)

Bearing dimensions	
Width (B)	45 mm
Outside diameter (D)	200 mm
Inside diameter (d)	95 mm

Operating conditions	
Type of movement	rotating
Relative speed (n_rel)	1.500 1/min

Temperatures	
Operating temperature (Theta)	70 °C
Ambient temperature (t)	40 °C
Environmental influence	0.5 (heavy)

#### Disclaimer

All rights are reserved with regard to this document, even in the event that a patent should be granted or a utility model registered. The document must be treated confidentially. Without our written consent, neither the document itself, nor copies thereof or any other renderings of the complete contents or of extracts therefrom may be made available to third parties or put to improper use by the recipient in any other way. The document has been prepared on the basis of your requirements as set forth above and our own assumptions. Our details take into account those risks which were apparent to us on the basis of your requirements as made available to us. The document has been prepared solely in connection with the purchase of our products. The results shown in the document have been worked out carefully and in accordance with the state of the art, but do not constitute an express or implied guaranty as to quality or durability in the legal sense. You are not dispensed thereby from checking the suitability of the products. We shall be liable for the details provided in the document only in the event of willful intent or negligence. If the document is part of a supply agreement, the liability provisions agreed there shall apply.

## Report for NU319-E-XL-M1-C3 All results refer to continuous 24/7 operation.

### Results sorted by relubrication interval (2/2 greases)

Non-Schaeffler High-Temperature Grease	
Initial grease quantity *	57,6 g/64 cm <sup>3</sup>
Quantity of relubrication per 365 days *	133,043 g/365 days
	147,825 cm <sup>3</sup> /365 days
Quantity of relubrication per 1000 operating hours *	15,188 g/1000 hours
	16,875 cm <sup>3</sup> /1000 hours
Grease service life *	~ 192 days
Quantity of relubrication per 30 days *	10,935 g/30 days
	12,15 cm <sup>3</sup> /30 days
Quantity of relubrication per 7 days *	2,552 g/7 days
	2,835 cm <sup>3</sup> /7 days
Lower temperature limit	-30 °C
Upper temperature limit	160 °C
Additive required	n.a.
Effective EP-additivation	n.a.
Low Friction	n.a.
Suitable for vibrations	n.a.
Support for sealing	n.a.
H1 registration (NSF-H1 kosher and halal certification)	n.a.

Arcanol TEMP90	
Mineral + PAO oil, NLGI3, Polyurea	
Initial grease quantity *	57,6 g/64 cm <sup>3</sup>
Quantity of relubrication per 365 days *	133,043 g/365 days
	147,825 cm <sup>3</sup> /365 days
Quantity of relubrication per 1000 operating hours *	15,188 g/1000 hours
	16,875 cm <sup>3</sup> /1000 hours
Grease service life *	~ 192 days
Quantity of relubrication per 30 days *	10,935 g/30 days
	12,15 cm <sup>3</sup> /30 days
Quantity of relubrication per 7 days *	2,552 g/7 days
	2,835 cm <sup>3</sup> /7 days
Viscosity ratio [κ]	4,13
Base oil viscosity at 40°C	148 mm <sup>2</sup> /s
Lower temperature limit	-40 °C
Upper temperature limit	160 °C
Additive required	no
Effective EP-additivation	no
Density	0,9 kg/dm <sup>3</sup>
Low Friction	0 (suitable)
Suitable for vibrations	0 (suitable)
Support for sealing	+ (highly suitable)
H1 registration (NSF-H1 kosher and halal certification)	no

#### Disclaimer

All rights are reserved with regard to this document, even in the event that a patent should be granted or a utility model registered. The document must be treated confidentially. Without our written consent, neither the document itself, nor copies thereof or any other renderings of the complete contents or of extracts therefrom may be made available to third parties or put to improper use by the recipient in any other way. The document has been prepared on the basis of your requirements as set forth above and our own assumptions. Our details take into account those risks which were apparent to us on the basis of your requirements as made available to us. The document has been prepared solely in connection with the purchase of our products. The results shown in the document have been worked out carefully and in accordance with the state of the art, but do not constitute an express or implied guaranty as to quality or durability in the legal sense. You are not dispensed thereby from checking the suitability of the products. We shall be liable for the details provided in the document only in the event of willful intent or negligence. If the document is part of a supply agreement, the liability provisions agreed there shall apply.

## Report for NU319-E-XL-M1-C3 All results refer to continuous 24/7 operation.

### Errors, Warnings & Notes

#### Warnings

Relubrication should be carried out once a year.

- Arcanol MOTION 2
- Arcanol MULTITOP
- Arcanol MULTI3
- Arcanol LOAD150

Very high kappa values and corresponding friction losses occur at the present operating speed for the following lubricating greases:

- Arcanol LOAD1000
- Arcanol TEMP120
- Arcanol TEMP200

The operating temperature is below the recommended minimum operating temperature for the following greases:

- Arcanol TEMP120 ( 70.0 °C < 80.0 °C )
- Arcanol TEMP200 ( 70.0 °C < 150.0 °C )

#### Notes

As the simplified load input via load levels has been used, the thermally safe operating speed as well as the static load safety are not checked.

Calculation of the grease service life and the relubrication interval corresponds to the catalog method. The internal geometry and the internal load distribution are not taken into consideration in the calculation. If you have any questions relating to selection of a suitable grease, please contact the Schaeffler engineering service. If the axis of rotation is vertical, the supply of lubricant to the contact must be checked.

In the Grease App, fatigue life is not considered or calculated. Please check this separately.

When calculating the amount of lubricant, only the volume of the bearing is taken into account, while the free space of the surrounding construction and the volume of the supply lines are not considered.

The specified grease quantities are only guide values, which may be deviated from based on practical experience. In case of questions, please contact the Schaeffler engineering service.

For the Non-Schaeffler Greases the individual properties are unknown. Therefore, criteria on the suitability of the grease are not checked for these greases (e.g., viscosity ratio, additivation, n\*dm-limits of the grease, thermally safe operating speed, suitability for the CONCEPT1 lubricator).

- Non-Schaeffler Multi-Purpose Grease
- Non-Schaeffler High-Temperature Grease

Since the selected grease grade is suitable for foodstuff applications, the values for the grease operating life and relubrication interval have been reduced by half.

- Arcanol FOOD2

#### Disclaimer

All rights are reserved with regard to this document, even in the event that a patent should be granted or a utility model registered. The document must be treated confidentially. Without our written consent, neither the document itself, nor copies thereof or any other renderings of the complete contents or of extracts therefrom may be made available to third parties or put to improper use by the recipient in any other way. The document has been prepared on the basis of your requirements as set forth above and our own assumptions. Our details take into account those risks which were apparent to us on the basis of your requirements as made available to us. The document has been prepared solely in connection with the purchase of our products. The results shown in the document have been worked out carefully and in accordance with the state of the art, but do not constitute an express or implied guaranty as to quality or durability in the legal sense. You are not dispensed thereby from checking the suitability of the products. We shall be liable for the details provided in the document only in the event of willful intent or negligence. If the document is part of a supply agreement, the liability provisions agreed there shall apply.