

DATE

13/08/2024

PRODUCER

R.E.M. SRL

CUSTOMER

HYDRO ALLUMINIUM SLIM

PRODUCT

ANSALDO DH560L27BD4 N COMM
2024 0632 N REM 06844

RESISTANCE TEST

	R min	R max	R	Temperature	Result	max dR %	dR %	Result dR
Phase 1	0	99999	0.30887	29.08	PASS	7.7	0.5	PASS
Phase 2			0.3073		PASS			
Phase 3			0.3073		PASS			

SURGE TEST

	V	Toll% L	L	dL %	Toll% Q	Q	dQ %	Result	T Q F %
Phase 1	1478	3.8	3.360 m	0.5	5	57.14	0	GO	99.5
Phase 2	1478		3.360 m			57.14		GO	
Phase 3	1478		3.377 m			57.14		GO	
Sample	0		0			0			

H. V. TEST

	V (V)	I Max (A)	I Meas(A)	Result
	1067	0	2	GO

MEGAOHMMETER TEST

	V (V)	R Min [MOhm]	R Meas [MOhm]	Result
	1067	1000	5	GO

SURGE 1.2/50 TEST

	V PK (V)	V 50u	Result
	964	482	GO

POLARIZATION INDEX TEST

	V PK (V)	Ri	Rf	K	Time (s)

