

Tab. 5.2 / Tab. 5.2

Motore Motor	Estremità d'Albero Shaft-End								Tenute sull'albero Shaft-Seals								Scatola - Morsettiera Terminal - Box					
	Linguetta Key								Lato Flangia Flange-end								Morsetti Terminals					
JM	D	DB	E	GA	F	GD	EB		Øi	Øe	H	Øi	Øe	H			N°-Ø	N°-KK	N°-XX	VA	VB	R
80	2-4	19	M6	40	21,5	6	6	30	20	35	7	20	35	7			6-M4	1-M20x1,5	1-tappo plug	31	87	87
90	S L 2-4-6	24	M8	50	27	8	7	40	25	40	7	25	40	7			6-M4	1-M25x1,5	1-tappo plug	31	106	106
100	L 2-4-6	28	M10	60	31	8	7	50	30	47	7	30	47	7			6-M4	1-M25x1,5	1-tappo plug	31	106	106
112	M 2-4-6	28	M10	60	31	8	7	50	30	47	7	30	47	7			6-M5	2-M25x1,5	--	35	114	122
132	S M 2-4-6	38	M12	80	41	10	8	65	40	62	7	40	62	7			6-M5	2-M32x1,5	--	43	114	122
160	M L 2-4-6	42	M16	110	45	12	8	90	45	62	12	45	62	12			6-M6	2-M40x1,5 1-M16x1,5		78	156	167

5.2. Serie GM trifase

5.2. GM series three-phase

B3

B5

B14

Estremità d'albero
Shaft end

Dis. 5.2 / Draw. 5.2

Tab. 5.3 / Tab. 5.3

Motore Motor	GM	Ingombri Principali Main Overall Dimensions						Piedi Feet								Flangia Flange								
		AC	AD	H	HD	LB	L	A	B	C	AB	BB	AA	CB	HA	K	IM	M	N _{j6}	P	LA	T	S	
160	M L 2-4-6	314	251	160	411	498 542	608 652	254	210 254	108	320	260 304	65	26	20	15	B5 B14	300 215	250 180	350 250	15 --	5 4	N°4 N°4 M12	19
180	M L 2-4-6	355	267	180	447	578 616	688 726	279	241 279	121	350	311 349	70	35	22	15	B5	300	250	350	15	5	N°4	19
200	L 2-4-6	397	299	200	499	669	779	318	305	133	390	370	70	32	25	18	B5	350	300	400	17	5	N°4	19
225	S 4	446	322	225	547	684	824	356	286	149	432	370	75	46	28	19	B5	400	350	450	20	5	N°8	19
225	M 2-4-6	446	322	225	547	709	819 849	356	311	149	433	395	75	46	28	19	B5	400	350	450	20	5	N°8	19
250	M 2-4-6	485	358	250	608	770	910	406	349	168	486	445	80	55	30	24	B5	500	450	550	22	5	N°8	19
280	S 2-4-6	547	387	280	667	842	982	457	368	190	545	485	85	69	35	24	B5	500	450	550	22	5	N°8	19
280	M 2-4-6	547	387	280	667	893	1033	457	419	190	545	536	85	69	35	24	B5	500	450	550	22	5	N°8	19
315	S 2-4-6	620	527	315	842	1054	1194 1224	508	406	216	630	570	120	84	45	28	B5	600	550	660	22	6	N°8	24
315	M 2-4-6	620	527	315	842	1164	1304 1334	508	457	216	630	680	120	84	45	28	B5	600	550	660	22	6	N°8	24
315	L 2-4-6	620	527	315	842	1164	1304 1334	508	508	216	630	680	120	84	45	28	B5	600	550	660	22	6	N°8	24
355	M 2-4-6	698	642	355	997	1346	1486 1556	610	560	254	730	750	120	68	52	28	B5	740	680	800	25	6	N°8	24
355	L 2-4-6	698	642	355	997	1346	1486 1556	610	630	254	730	750	120	68	52	28	B5	740	680	800	25	6	N°8	24
355	X 2-4-6	770	765	355	1120	1710	1850 1920	630	800	224	760	1140	135	88	52	35	B5	840	780	900	28	6	N°8	24
400	M 4-6	860	680	400	1080	1770	1980	686	630	280	806	1090	120	57	45	35	B5	940	880	1000	25	6	N°8	28