

CENTRIFUGAL PUMPS
Aral C-3000 pump Star/Delta


Made in cast iron. Mechanical seal in stainless steel. IP-54 motor protection. Stainless steel AISI-316 shaft. With stainless steel AISI-304 strainer basket. 3000 rpm. Connections PN 16 according to DIN 2501.



Aral C-3000 3 HP
Aral C-3000 4 HP
Aral C-3000 5.5 HP Connection DN 80-3"
Aral C-3000 5.5 HP Connection DN 100-4"
Aral C-3000 7.5 HP
Aral C-3000 10 HP
Aral C-3000 12.5 HP
Aral C-3000 15 HP

Discount group	Code	Unit £
F	01193	3,204.00
F	01195	3,574.00
F	01197	4,219.00
F	01199	4,600.00
F	01201	5,024.00
F	01203	5,291.00
F	01205	5,614.00
F	01207	6,195.00

Code	Power	Connection	Voltage	m.w.h.					
				8	10	12	14	16	20
				m³/h					
01193	2.20 kW (3 HP)	DN 90-3"	230/400 V III	59	54	46	40	30	0
01195	2.95 kW (4 HP)	DN 80-3"	400/690 V III	67	61	55	48	40	0
01197	4.00 kW (5.5 HP)	DN 80-3"	400/690 V III	78	72	66	60	52	0
01199	4.00 kW (5.5 HP)	DN 100-4"	400/690 V III	100	89	70	60	48	0
01201	5.50 kW (7.5 HP)	DN 100-4"	400/690 V III	126	115	100	80	60	0
01203	7.50 kW (10 HP)	DN 100-4"	400/690 V III	145	140	123	107	86	0
01205	8.70 kW (12.5 HP)	DN 125-5"	400/690 V III	165	158	149	135	115	0
01207	11.04 kW (15 HP)	DN 125-5"	400/690 V III	195	190	175	160	140	0

Aral C-1500 pump Star/Delta


Made in cast iron. Mechanical seal in stainless steel. IP-54 motor protection. Stainless steel AISI- 316 shaft. With stainless steel AISI-304 strainer basket. Connections PN 16 according to DIN 2501. 1,450 rpm.



Aral C-1500 4 HP
Aral C-1500 5.5 HP
Aral C-1500 7.5 HP
Aral C-1500 10 HP
Aral C-1500 12.5 HP
Aral C-1500 20 HP
Aral C-1500 25 HP

Discount group	Code	Unit £
F	01210	4,116.00
F	01212	5,487.00
F	01216	6,132.00
F	01218	6,342.00
F	01220	7,938.00
F	01224-1800	14,041.00
F	01226-1800	17,426.00

Code	Power	Suction Connection	Discharge Connection	Voltage	m.w.h.					
					10	12	14	16	18	20
					m³/h					
01210	3.00 kW (4 HP)	DN 80-3"	DN 65-2½"	400/690 V III	68	60	45	0	0	0
01212	4.00 kW (5.5 HP)	DN 80-3"	DN 65-2½"	400/690 V III	88	80	70	58	0	0
01216	5.50 kW (7.5 HP)	DN 100-4"	DN 80-3"	400/690 V III	115	101	87	70	0	0
01218	7.50 kW (10 HP)	DN 100-4"	DN 80-3"	400/690 V III	150	140	125	115	0	0
01220	9.20 kW (12.5 HP)	DN 125-5"	DN 100-4"	400/690 V III	192	175	155	130	0	0