

ELECTRIC DC MOTORS NEW - AVAILABLE IN OUR STOREHOUSE

TYPE	FRAME	p	n	VA	IA	VF	IF	SHAFT END	COOL.	P.D.	I.M.	I.C.	BRAND
	mm	kW	rpm	V	A	V	A	mm					
L3B400K-2I	400	600	800-1800	520	1236	220	16,74	ø130x250	IC06	IP23S	B3	H	STIPAF
L1B225L-A5	225	318	1905-3000	440	768	340-170	6,0-12,0	ø85x170	IC06	IP23S	B3	H	STIPAF
L1B225M-B5	225	275	1775-3000	400	736	340-170	5,2-10,4	ø85x170	IC06	IP23S	B3	H	STIPAF
L3B225S-K	225	133	957-2400	400	372	330	7,40	ø80x170	IC06	IP23S	B35	H	STIPAF
L1B200X-B5	200	236	2074-3000	440	576	340-170	5,7-11,4	ø75x140	IC06	IP23S	B35	H	STIPAF
L2B160M-B	160	72	1874-3000	440	182	340-170	3,16-6,32	ø55x110	IC06	IP23S	B35	H	STIPAF
L1B160M-A1	160	93,8	2631	400	256	330	3,16	ø55x110	IC06	IP23S	B3	H	STIPAF
L1B160S-B	160	68,2	2302	440	171	195	4,88	ø55x110	IC06	IP23S	B3	H	STIPAF
Z4-160-32	160	49,5	2710-3500	400	137	180	4,01	ø48x110	IC06	IP21S	B3	F	WUXI
L1B112X-H	112	15,5	2075	400	44,7	220	1,41	ø38x80	IC06	IP23S	B35	H	STIPAF
L1B90L	90	5,1	1730-4000	400	15,5	190	1,8	ø28x60	IC06	IP23S	B34	H	STIPAF
L1G80X-L	80	1,47	3000	280	6,7	220-110	1,17-0,585	ø19x40	IC01	IP23S	B34	H	STIPAF
L1A80L	80	2,2	2600	280	8,8	190	1,3	ø24x50	IC06	IP23S	B34	H	STIPAF
L1A80S-Z	80	2,0	1950	440	5,9	220	0,8	ø24x50	IC06	IP23S	B34	H	STIPAF
L1A80S-H	80	2,0	3000	170	14	190	1,1	ø24x50	IC06	IP23S	B35	H	STIPAF