

ELECTRIC DC MOTORS - AVAILABLE IN STIPAF WAREHOUSE - SUBJECT TO PRIOR SALE

TYPE	FRAME	P	n	U	I	UF	IF	OUTPUT SHAFT	BEARING D.E.	COOL.	I.C.	
	mm	kW	rpm	V	A	V	A	mm	kind			
L3B355X-A	355	622	860-1400	440	1510	220	27,7	ø110x210	6324 C3	IC06	H	AVAILABLE
L3B315P-J	315	314	411-800	440	814	340	14,4	ø100x210	6322 C3	IC06	H	AVAILABLE
L3B250-PB	250	400	1355-2500	560	760	340	10,8	ø95x170	6320ZZ C3	IC06	H	SOON
L1B225M-B0	225	314	2054-3000	460	725	340-170	5,2-10,4	ø85x170	NU318E C3	IC06	H	AVAILABLE
L1B225M-E	225	228	1453	440	558	340-170	5,2-10,4	ø85x170	NU318E C3	IC06	H	SOON
L1B200M-C	200	192	2269	400	512	330	4,52	ø75x140	NU316E C3	IC06	H	SOON
L1B180X-E	180	156	1950	440	384	340-170	5,3-10,6	ø65x140	NU314E C3	IC06	H	SOON
L1B160P-D	160	38,5	750-1100	400	117	340	3,93	ø55x110	6312ZZ C3	IC06	H	AVAILABLE
L1B160X-A1	160	103	2234	440	256	340-170	3,5-7,0	ø55x110	NU312E C3	IC06	H	SOON
L1B160M-A1	160	93,8	2631	400	256	330	3,16	ø55x110	NU312E C3	IC06	H	SOON
L1B132S-D	132	36,6	2444	440	92,4	340-170	2,6-5,2	ø48x110	NU310E C3	IC06	H	SOON
L1A80L	80	2,2	2600	280	8,8	190	1,3	ø24x50	6305ZZ C3	IC06	H	AVAILABLE
L1A80S-Z	80	2,0	1950	440	5,9	220	0,8	ø24x50	6305ZZ C3	IC06	H	AVAILABLE
L1A80S-H	80	2,0	3000	170	14	190	1,1	ø24x50	6305ZZ C3	IC06	H	AVAILABLE
L1G80X-L	80	1,47	3000	280	6,7	220-110	1,17-0,585	ø19x40	6305ZZ C3	IC01	H	AVAILABLE