

01 - Listino FELM 05.2011

Motori Standard

Three Phase Squirrel Cage Induction Motors

Voltage 230/400V,400/690V, 50Hz, Insulation class F, temperature Rise B, Protection IP55, mounting IM B3, SKF or NSK bearing

According to EN 60034-30



MA/FA2 : Aluminium
Y2/F2 : Cast Iron

2 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA 63B	0,25	194	204	210
MA 71A	0,37	221	232	238
MA 71B	0,55	229	240	247
FA2 80S	0,75	329	345	362
FA2 80L	1,1	364	382	400
FA2 90S	1,5	440	462	484
FA2 90L	2,2	502	527	552
FA2 100L	3	715	751	787
FA2 112M	4	833	875	916
FA2 132S1	5,5	1.230	1.292	1.353
FA2 132S2	7,5	1.377	1.446	1.515
F2 160M	11	2.158	2.266	2.374
F2 160M2	15	2.360	2.478	2.596
F2 160L	18,5	2.675	2.809	2.943
F2-180M	22	3.715	3.901	4.087
F2-200L1	30	4.963	5.211	5.459
F2-200L2	37	5.315	5.581	5.846
F2-225M	45	6.385	6.704	7.023
F2-250M	55	7.837	8.229	8.620
F2-280S	75	9.554	10.032	10.509
F2-280M	90	10.413	10.934	11.454
F2-315S	110	17.576	18.455	19.334
F2-315M	132	19.274	20.238	21.201
F2-315L	160	20.694	21.729	22.763
F2-315LX	200	23.188	24.347	25.506
F2-355M	250	35.230	36.991	38.753
F2-355L	280	37.814	39.705	41.596
F2-355LX	315	38.081	39.985	41.890
Y2 355L3	355	56.050	61.655	67.821
Y2 400M	400	69.933	76.926	84.619
Y2 400MX	450	78.327	86.160	94.776
Y2 400L	500	86.651	95.316	104.847
Y2 400LX	560	91.766	100.943	111.037

4 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA 63B	0,18	200	209	216
MA 71A	0,25	233	244	252
MA 71B	0,37	243	256	262
FA2 80L	0,75	391	411	430
FA2 90S	1,1	461	484	507
FA2 90L	1,5	546	573	601
FA2 100L1	2,2	692	727	761
FA2 100L2	3	785	824	864
FA2 112M	4	970	1.019	1.067
FA2 132S	5,5	1.241	1.303	1.365
FA2 132M	7,5	1.492	1.567	1.641
F2 160M	11	2.282	2.396	2.510
F2 160L	15	2.666	2.799	2.933
F2-180M	18,5	3.603	3.783	3.963
F2-180L	22	3.949	4.146	4.344
F2-200M	30	5.109	5.365	5.620
F2-225S	37	6.167	6.475	6.783
F2-225M	45	6.671	7.004	7.338
F2-250M	55	8.282	8.697	9.111
F2-280S	75	10.468	10.991	11.515
F2-280M	90	11.441	12.013	12.585
F2-315S	110	17.578	18.457	19.336
F2-315M	132	18.987	19.936	20.885
F2-315L	160	20.856	21.899	22.942
F2-315LX	200	23.723	24.909	26.095
F2-355M	250	36.820	38.661	40.502
F2-355L	280	39.799	41.789	43.779
F2-355LX	315	40.018	42.018	44.019
F2-355LY	355	42.832	44.974	47.116
Y2 400M	400	68.423	75.266	82.792
Y2 400MX	450	77.336	85.070	93.577
Y2 400L	500	86.486	95.134	104.648
Y2 400LX	560	101.529	111.682	122.850
Y2 400LY	630	116.572	128.230	141.053

Documentazione Tecnica

: Nostro standard (Manuale uso e manutenzione - dichiarazione CE)

Optionals e Varianti su Ordine

: Consultare "08 Listino accessori 05.2011"

Trasformazioni/varianti su motori a magazzino

: Consultare "02 Listino accessori 05.2011"

UFFICI e MAGAZZINI : INVERUNO - Via Morandi Z.I. - Tel. 02 97 289 454 - Fax 02 97 289 923

01 - Listino Felm - Rev. Maggio 2011

01 - Listino FELM 05.2011

Motori Standard

Three Phase Squirrel Cage Induction Motors

Voltage 230/400V, 400/690V, 50Hz, Insulation class F, temperature Rise B,

Protection IP55, mounting IM B3, SKF or NSK bearing

According to EN 60034-30



MA/FA2 : Aluminium

Y2/F2 : Cast Iron

6 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA71A	0,18	217	228	234
MA 71B	0,25	251	264	271
MA 80A	0,37	294	309	317
MA 80B	0,55	317	332	342
FA2 90S	0,75	455	478	501
FA2 90L	1,1	547	574	602
FA2 100L	1,5	642	674	706
FA2 112M	2,2	855	898	941
FA2 132S	3	1.072	1.126	1.179
FA2 132M1	4	1.233	1.295	1.356
FA2 132M2	5,5	1.462	1.535	1.608
F2 160M	7,5	2.249	2.361	2.474
F2 160L	11	2.559	2.687	2.815
F2-180L	15	3.540	3.717	3.894
F2-200L1	18,5	4.281	4.495	4.709
F2-200L2	22	4.655	4.888	5.121
F2-225M	30	6.373	6.692	7.011
F2-250M	37	7.396	7.766	8.135
F2-280S	45	10.017	10.518	11.019
F2-280M	55	11.106	11.661	12.216
F2-315S	75	16.704	17.539	18.374
F2-315M	90	18.221	19.132	20.043
F2-315L	110	20.430	21.452	22.473
F2-315LX	132	22.153	23.261	24.369
F2-355M	160	31.727	33.313	34.899
F2-355MX	180	33.307	34.972	36.638
F2-355MY	200	33.818	35.509	37.199
F2-355L	220	36.011	37.812	39.613
F2-355LX	250	38.444	40.367	42.289
F2-355LY	280	40.260	42.273	44.286
Y2 400M	315	74.473	81.920	86.016
Y2 400MX	355	85.310	93.840	98.532
Y2 400L	400	94.318	103.749	108.937
Y2 400LX	450	107.276	118.004	123.904
Y2 400LY	500	119.195	131.115	137.671

8 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA 80A	0,18	289	303	312
MA 80B	0,25	310	325	335
MA 90SN	0,37	465	489	502
MA 90LN	0,55	542	568	585
MA 100LA	0,75	628	661	679
MA 100LB	1,1	753	790	813
MA 112M	1,5	864	908	934
MA 132S	2,2	1.141	1.198	1.232
MA 132M	3	1.362	1.430	1.471
Y2 160MA	4	1.524	1.600	1.645
Y2 160MB	5,5	1.876	1.969	2.026
Y2 160L	7,5	2.332	2.449	2.519
Y2 180L	11	3.141	3.297	3.392
Y2 200L	15	4.037	4.240	4.360
Y2 225S	18,5	4.919	5.164	5.312
Y2 225M	22	6.066	6.369	6.552
Y2 250M	30	7.809	8.200	8.434
Y2 280S	37	9.408	9.879	10.161
Y2 280M	45	11.048	11.601	11.932
Y2 315S	55	14.074	15.481	16.256
Y2 315M	75	19.146	21.061	22.114
Y2 315LA	90	23.727	26.099	27.404
Y2 315LB	110	26.439	29.083	30.537
Y2 355MA	132	27.633	30.396	31.916
Y2 355MB	160	29.776	32.754	34.392
Y2 355L	200	34.606	38.066	39.969
Y2 400M	250	72.493	79.742	83.729
Y2 400MX	280	79.741	87.715	92.101
Y2 400L	315	86.799	95.479	100.253
Y2 400LX	355	95.479	105.027	110.279
Y2 400LY	400	113.117	124.429	130.651

Documentazione Tecnica

: Nostro standard (Manuale uso e manutenzione - dichiarazione CE)

Optionals e Varianti su Ordine

: Consultare "08 Listino accessori 05.2011"

Trasformazioni/varianti su motori a magazzino

: Consultare "02 Listino accessori 05.2011"

UFFICI e MAGAZZINI : INVERUNO - Via Morandi Z.I. - Tel. 02 97 289 454 - Fax 02 97 289 923