

01 - Listino FELM 05.2011

Motori Standard

Three Phase Squirrel Cage Induction Motors

Voltage 230/400V,400/690V, 50Hz, Insulation class F, temperature Rise B,

Protection IP55, mounting IM B3, SKF or NSK bearing

According to EN 60034-30



MA/FA2 : Aluminium

Y2/F2 : Cast Iron

2 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA 63B	0.25	29	31	31
MA 71A	0.37	33	35	36
MA 71B	0.55	34	36	37
FA2 80S	0.75	49	52	54
FA2 80L	1.1	55	57	60
FA2 90S	1.5	66	69	73
FA2 90L	2.2	75	79	83
FA2 100L	3	107	113	118
FA2 112M	4	125	131	137
FA2 132S1	5.5	185	194	203
FA2 132S2	7.5	207	217	227
F2 160M	11	324	340	356
F2 160M2	15	354	372	389
F2 160L	18.5	401	421	441
F2-180M	22	557	585	613
F2-200L1	30	744	782	819
F2-200L2	37	797	837	877
F2-225M	45	958	1.006	1.053
F2-250M	55	1.176	1.234	1.293
F2-280S	75	1.433	1.505	1.576
F2-280M	90	1.562	1.640	1.718
F2-315S	110	2.636	2.768	2.900
F2-315M	132	2.891	3.036	3.180
F2-315L	160	3.104	3.259	3.415
F2-315LX	200	3.478	3.652	3.826
F2-355M	250	5.284	5.549	5.813
F2-355L	280	5.672	5.956	6.239
F2-355LX	315	5.712	5.998	6.283
Y2 355L3	355	8.408	9.248	10.173
Y2 400M	400	10.490	11.539	12.693
Y2 400MX	450	11.749	12.924	14.216
Y2 400L	500	12.998	14.297	15.727
Y2 400LX	560	13.765	15.141	16.656

4 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA 63B	0.18	30	31	32
MA 71A	0.25	35	37	38
MA 71B	0.37	36	38	39
MA 80A	0.55	44	46	48
FA2 80L	0.75	59	62	65
FA2 90S	1.1	69	73	76
FA2 90L	1.5	82	86	90
FA2 100L1	2.2	104	109	114
FA2 100L2	3	118	124	130
FA2 112M	4	146	153	160
FA2 132S	5.5	186	195	205
FA2 132M	7.5	224	235	246
F2 160M	11	342	359	377
F2 160L	15	400	420	440
F2-180M	18.5	540	567	594
F2-180L	22	592	622	652
F2-200M	30	766	805	843
F2-225S	37	925	971	1.017
F2-225M	45	1.001	1.051	1.101
F2-250M	55	1.242	1.304	1.367
F2-280S	75	1.570	1.649	1.727
F2-280M	90	1.716	1.802	1.888
F2-315S	110	2.637	2.769	2.900
F2-315M	132	2.848	2.990	3.133
F2-315L	160	3.128	3.285	3.441
F2-315LX	200	3.558	3.736	3.914
F2-355M	250	5.523	5.799	6.075
F2-355L	280	5.970	6.268	6.567
F2-355LX	315	6.003	6.303	6.603
F2-355LY	355	6.425	6.746	7.067
Y2 400M	400	10.264	11.290	12.419
Y2 400MX	450	11.600	12.760	14.036
Y2 400L	500	12.973	14.270	15.697
Y2 400LX	560	15.229	16.752	18.428
Y2 400LY	630	17.486	19.234	21.158

Documentazione Tecnica

: Nostro standard (Manuale uso e manutenzione - dichiarazione CE)

Optionals e Varianti su Ordine

: Consultare "08 Listino accessori 05.2011"

Trasformazioni/varianti su motori a magazzino

: Consultare "02 Listino accessori 05.2011"

UFFICI e MAGAZZINI : INVERUNO - Via Morandi Z.I. - Tel. 02 97 289 454 - Fax 02 97 289 923

01 - Listino Felm - Rev. Maggio 2011

01 - Listino FELM 05.2011

Motori Standard

Three Phase Squirrel Cage Induction Motors

Voltage 230/400V, 400/690V, 50Hz, Insulation class F, temperature Rise B,

Protection IP55, mounting IM B3, SKF or NSK bearing

According to EN 60034-30



MA/FA2 : Aluminium

Y2/F2 : Cast Iron

6 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA71A	0.18	33	34	35
MA 71B	0.25	38	40	41
MA 80A	0.37	44	46	48
MA 80B	0.55	47	50	51
FA2 90S	0.75	68	72	75
FA2 90L	1.1	82	86	90
FA2 100L	1.5	96	101	106
FA2 112M	2.2	128	135	141
FA2 132S	3	161	169	177
FA2 132M1	4	185	194	203
FA2 132M2	5.5	219	230	241
F2 160M	7.5	337	354	371
F2 160L	11	384	403	422
F2-180L	15	531	558	584
F2-200L1	18.5	642	674	706
F2-200L2	22	698	733	768
F2-225M	30	956	1.004	1.052
F2-250M	37	1.109	1.165	1.220
F2-280S	45	1.503	1.578	1.653
F2-280M	55	1.666	1.749	1.832
F2-315S	75	2.506	2.631	2.756
F2-315M	90	2.733	2.870	3.007
F2-315L	110	3.065	3.218	3.371
F2-315LX	132	3.323	3.489	3.655
F2-355M	160	4.759	4.997	5.235
F2-355MX	180	4.996	5.246	5.496
F2-355MY	200	5.073	5.326	5.580
F2-355L	220	5.402	5.672	5.942
F2-355LX	250	5.767	6.055	6.343
F2-355LY	280	6.039	6.341	6.643
Y2 400M	315	11.171	12.288	12.902
Y2 400MX	355	12.796	14.076	14.780
Y2 400L	400	14.148	15.562	16.341
Y2 400LX	450	16.091	17.701	18.586
Y2 400LY	500	17.879	19.667	20.651

8 poli Modello	kW	Forma		
		B3	B5/V1	B3/B5
MA 80A	0.18	43	45	47
MA 80B	0.25	47	49	50
MA 90SN	0.37	70	73	75
MA 90LN	0.55	81	85	88
MA 100LA	0.75	94	99	102
MA 100LB	1.1	113	119	122
MA 112M	1.5	130	136	140
MA 132S	2.2	171	180	185
MA 132M	3	204	215	221
Y2 160MA	4	229	240	247
Y2 160MB	5.5	281	295	304
Y2 160L	7.5	350	367	378
Y2 180L	11	471	495	509
Y2 200L	15	606	636	654
Y2 225S	18.5	738	775	797
Y2 225M	22	910	955	983
Y2 250M	30	1.171	1.230	1.265
Y2 280S	37	1.411	1.482	1.524
Y2 280M	45	1.657	1.740	1.790
Y2 315S	55	2.111	2.322	2.438
Y2 315M	75	2.872	3.159	3.317
Y2 315LA	90	3.559	3.915	4.111
Y2 315LB	110	3.966	4.362	4.581
Y2 355MA	132	4.145	4.559	4.787
Y2 355MB	160	4.466	4.913	5.159
Y2 355L	200	5.191	5.710	5.995
Y2 400M	250	10.874	11.961	12.559
Y2 400MX	280	11.961	13.157	13.815
Y2 400L	315	13.020	14.322	15.038
Y2 400LX	355	14.322	15.754	16.542
Y2 400LY	400	16.968	18.664	19.598

Documentazione Tecnica

: Nostro standard (Manuale uso e manutenzione - dichiarazione CE)

Optionals e Varianti su Ordine

: Consultare "08 Listino accessori 05.2011"

Trasformazioni/varianti su motori a magazzino

: Consultare "02 Listino accessori 05.2011"

UFFICI e MAGAZZINI : INVERUNO - Via Morandi Z.I. - Tel. 02 97 289 454 - Fax 02 97 289 923