

MS152

DIMENSIONI D'INGOMBRO

OVERALL DIMENSIONS

DIMENSIONES GENERALES

Motore tipo Motor type Motor tipo	Potenza Output Potencia		L mm	Peso Weight Peso kg	J kg m ²
	kW	HP			
MS152-2	1,5	2	485	32.4	0.00394
MS152-3	2,2	3	485	32.5	0.00394
MS152-4	3	4	502	36	0.00424
MS152-5	4	5,5	521	40	0.00457
MS152-7	5,5	7,5	552	44	0.00512
MS152-10	7,5	10	595	49	0.00587
MS152-12	9	12,5	635	54	0.00657
MS152-15	11	15	685	60	0.00745
MS152-17	13	17,5	725	62	0.00815
MS152-20	15	20	775	65	0.00950
MS152-25	18,5	25	875	81	0.01126
MS152-30	22	30	965	91	0.01284
MS152-35	26	35	1055	103	0.01442
MS152-40	30	40	1135	109	0.01582
MS153-50	37	50	1225	120	0.01898

ALBERO

Albero dentato: 15 denti, modulo 1,5875, angolo di pressione 30°, accoppiamento ANSI B.92.1 classe 5. Conforme a Norme NEMA 6".

SHAFT

Spline shaft: 15 teeth, module 1.5875, 30° pressure angle, coupling ANSI B.92.1, class 5. In conformity with NEMA 6" standards.

EJE

Eje estriado: 15 dientes, modulo 1,5875, ángulo de presión 30°, acoplamiento ANSI B.92.1 clase 5, en conformidad a las normas NEMA 6".

CAVI DEL MOTORE

MOTOR CABLES • CABLES DEL MOTOR

DOL		Y - Δ	
N° 1 cavo tripolare / No. 1 three-pole cable N° 1 cable tripolar chato		N° 2 cavi tripolari / No. 2 three-pole cable N° 2 cables tripolares	
Corrente Nominale Nominal current Corriente nominal	Sezione del cavo Cable cross-section Sección transversal cable	Corrente Nominale Nominal current Corriente nominal	Sezione del cavo Cable cross-section Sección transversal cable
< 26 A	3 x 2,5	< 45 A	3 x 2,5
26 - 36 A	3 x 4	45 - 62 A	3 x 4
36 - 50 A	3 x 6	62 - 86 A	3 x 6
50 - 75 A	3 x 10	86 - 130 A	3 x 10

Sporgenza cavi dal motore = 3 m • Cable for connecting motor: 3 m long • Salida de los cables = 3m

DIMENSIONI DEI CAVI

CABLE DIMENSIONS • DIMENSIONES DE LOS CABLES

Sezione cavo Cable cross-section Sección transversal cable mm ²	Dimensioni esterne External dimensions Dimensiones externas	
	L (mm)	H (mm)
3 x 2,5	13,1	6,3
3 x 4	17,2	7,6
3 x 6	19,4	8,6
3 x 10	24,2	10,2

