

Motori asincroni

Disegni quotati

Motori 1PH7 Ventilazione assistita

Per motore Dimensioni in mm (pollici)

Altezza d'asse	Tipo	DIN IEC	a B	a ₁ P	b A	b ₁ N	c LA	e ₁ M	f AB	f ₁ T	h H	i ₂ -	k LB	k ₁ -	m BA	m ₁ -	m ₂ -	n AA	p HD
1PH7, forma costruttiva IM B35, ventilazione assistita																			
100	1PH7101	202,5	250	160	180	11	215	196	4	100	80	411	435	52	64	27	39	220	
	1PH7103	(7,97)	(9,84)	(6,30)	(7,09)	(0,43)	(8,46)	(7,72)	(0,16)	(3,94)	(3,15)	(16,18)	(17,13)	(2,05)	(2,52)	(1,06)	(1,54)	(8,66)	
	1PH7105	297,5										506	529						
	1PH7107	(11,71)										(19,92)	(20,83)						
132	1PH7131	265,5	350	216	250	14	300	260	5	132	110	538	561	63	75	33	52	275	
	1PH7133	(10,45)	(13,78)	(8,50)	(9,84)	(0,55)	(11,81)	(10,24)	(0,20)	(5,20)	(4,33)	(21,18)	(22,09)	(2,48)	(2,95)	(1,30)	(2,05)	(10,83)	
	1PH7135	350,5										623	646						
	1PH7137	(13,80)										(24,53)	(25,43)						
160	1PH7163	346,5	400	254	300	17	350	314	5	160	110	640	663	78	81	42	62	330	
	1PH7167	(13,64)	(15,75)	(10,00)	(11,81)	(0,67)	(13,78)	(12,36)	(0,20)	(6,30)	(4,33)	(25,20)	(26,10)	(3,07)	(3,19)	(1,65)	(2,44)	(12,99)	
		406,5										700	723						
		(16,00)										(27,56)	(28,46)						

Estremità d'albero lato AS

Altezza d'asse	Tipo	DIN IEC	s K	s ₂ S	s ₃ -	w ₁ C	d D	d ₆ -	l E	t GA	u F
100	1PH7101	12	14	PG29	40	38	M12	80	41	10	
	1PH7103	(0,47)	(0,55)		(1,57)	(1,50)		(3,15)	(1,61)	(0,39)	
	1PH7105										
	1PH7107										
132	1PH7131	12	18	PG36	50	42	M16	110	45	12	
	1PH7133	(0,47)	(0,71)		(1,97)	(1,65)		(4,33)	(1,77)	(0,47)	
	1PH7135										
	1PH7137										
160	1PH7163	14	18	PG42	64	55	M20	110	59	16	
	1PH7167	(0,47)	(0,71)		(2,52)	(2,17)		(4,33)	(2,32)	(0,63)	

Per le dimensioni differenti ed aggiuntive dei motori 1PH7 con DRIVE-CLiQ vedere Motori 1PH7 con DRIVE-CLiQ

1PH710
1PH713
1PH716