



Data sheet

30.01.2009

MADE WITH VERSION: 6.02

Manufacturer

Customer

VEM motors GmbH
Carl-Friedrich-Gauß-Straße 1
D-38855 Wernigerode

Three-phase motors with slipring rotor, low voltage version
mode of operation S3, intermittent duty

Type	SPEH 225 M6 HW			
Design output	(kW)	28	25	22
Duty type	S3-25/40/60/100% ED			
Number of poles	(-)	6		
Design frequency	(Hz)	50		
Design speed	[rpm]	965	970	973
Max. speed	[rpm]	2080		
stator voltage	(V)	400		
Stator connection	(-)	Y		
Stator design current	(A)	55.5	49.5	45.0
Power factor	(-)	0,84	0,83	0,81
Efficiency	(%)	87	87,5	87,5
Relative pull-out torque	(-)	2,8	3,2	3,6
Rotor voltage	(V)	250		
Rotor connection	(-)	Y		
Rotor current	(A)	69	62	55
Rotor resistance	[Ω]	0,0499		
Th. cl.		155(F/B)		
Coolant temperature	(°C)	40°C		
Altitude above sea level	(m)	1000m		
Degree of protection		IP54		
Moment of inertia	(kgm ²)	0,464		
Motor weight	(kg)	305		
Bearing, D-side		6313 C3		
Bearing, N-side		6313 C3		
Relubrication interval	(h)			
Grease type	ASONIC GHY72			
Grease amount	(g)			
Brush holder		14487 01		
Carbon brush		01502 01		
Slip-ring body		12302 01		
Special details to bearings 1		none		
Special details to bearings 2		Fixed bearing, N-side		
Bearing monitoring		none		
Winding protection		none		
Winding protection 2		none		
Anti-condensation heating		none		
Special versions 1		none		
Special versions 2		none		
Special versions 3		none		
Special versions 4		none		
Limit values to vibration velocity		Class A		
Balancing with half key				
Colour system		World wide		
Colour shade		RAL 7031 blue-grey		
Layer thickness		70 µm		

Delivery conditions and/or official regulations: DIN EN 60034-1

This document was produced electronically, all specifications are valid only after confirmation of the manufacturer

Seite 1/2

VEM motors GmbH
Carl-Friedrich-Gauß-Straße 1
D-38855 Wernigerode
Postfach-Nr. 101252
D-38842 Wernigerode

Telefon: 0 39 43 / 68-0
Telefax: 0 39 43 / 68 21 20
E-Mail: motors@vem-group.com
www.vem-group.com

Geschäftsführer:
Jürgen Sander
Dr. Dietmar Puschkeit
Dr. Susanne Frieß

Rechtsform: GmbH
Sitz: Wernigerode
Amtsgericht
Stendal HRB 112964
Ust.-Id. Nr. DE 212 649 455

Commerzbank AG
Dresden
BLZ 850 400 00
Kto.-Nr. 800 15 88

Dresdner Bank AG
Wernigerode
BLZ 800 800 00
Kto.-Nr. 350 50 30 00

Deutsche Bank AG
Wernigerode
BLZ 810 700 00
Kto.-Nr. 250 04 03



Data sheet


30.01.2009

MADE WITH VERSION: 6.02

Three-phase motors with slipping rotor, low voltage version
mode of operation S3, intermittent duty


SPEH 225 M6 HW

Mounting position



Type of mounting: IM B3
Flange: -
Position of terminal box: on the top

Terminal box: KK 100 A
Cable gland O: 1 xSealing plug
Cable gland OA: M50x1,5
connection cable: max. Ø 35 mm



Motor

A	AA	AB	AC	AD	B	B'	BA	BA'	BB	C	CA	K	K'
356	75	413	390	-	311	-	75	75	368	149	-	19	19

Terminal box

L	LC	H	HA	HD	HH	BI	AG	AG'	LL	LL'	BE	AH
957	-	225	25	525	331	40	213	310	207	146	-	-

Flange

P	N	LA	M	T	S	H	N	D	DA
-	-	-	-	-	-	-0,5	h6	m6	m6

Tolerances

Shaft-DS

D	E	GA	F	DB
60	140	64	18	DIN 332-DS M20-

Shaft-NS

DA	EA	GC	FA
-	-	-	-

DB...Centre hole

Delivery conditions and/or official regulations: DIN EN 60034-1

This document was produced electronically, all specifications are valid only after confirmation of the manufacturer